



Temperature range: **+2°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290**

Name	LUNA 60	LUNA 90	LUNA 120	LUNA 188	LUNA 313
Code	BL101.144	BL102.144	BL103.144	BL104.144	BL105.144
Length [mm]	600	900	1200	1880	3130
Height [mm]	1440±10	1440±10	1440±10	1440±10	1440±10
Depth [mm]	660	660	660	660	660
Capacity [dm ³]	180	270	370	600	1000
Display area [m ²]	0,79	1,19	1,64	2,66	4,44
Total Display Area (TDA) [m ²]	-	-	-	-	-
Temp. range [°C]	(+2 ± +10°C)	(+2 ± +10°C)	(+2 ± +10°C)	(+2 ± +10°C)	(+2 ± +10°C)
Temp. class	-	-	-	-	-
Climate class	-	-	-	-	-
Energy efficiency class	D	D	D	D	D
Refrigerant	R290 /	R290 /	R290 /	R290 /	R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	886	1408	1508	1860	2412

Standard equipment

internal cooling aggregate R290

dynamic cooling (ventilated)

exterior, interior and exposition shelves made of coloured coated steel - different colours available (Igloo pattern book)

price stripes – different colors available (IGLOO pattern book)

ecological polyurethane foam insulation

external glass elements made of combined glass with argon filling and black, white or gray RAL7042 silkscreen

upper interior lighting + backlight of each shelf - LED lamp (colour of choice: white, confectionery or meaty)

automatic defrost

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

external housing color – different colors available (IGLOO pattern book)

external housing made of stainless steel

interior colour - possibility of choosing the color (IGLOO pattern book)

interior and frame made of stainless steel sheet

exposition shelves on frame made of stainless steel

powder painted evaporator

electronic temperature recorder + software

temperature recorder wire

