



Temperature range: **+3°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Name	SUMBA 1.0	SUMBA 1.5	SUMBA 2.0	SUMBA 2.5
Code	SU100	SU101	SU102	SU103
Length [mm]	1060	1500	2040	2520
Height [mm]	1260+/10	1260+/10	1260+/10	1260+/10
Depth [mm]	940	940	940	940
Capacity [dm <sup>3</sup> ]	120	195	260	335
Display area [m <sup>2</sup> ]	0,65	0,95	1,3	1,61
Total Display Area (TDA) [m <sup>2</sup> ]	-	-	-	-
Temp. range [°C]	(+3 ± +10°C)	(+3 ± +10°C)	(+3 ± +10°C)	(+3 ± +10°C)
Temp. class	-	-	-	-
Climate class	-	-	-	-
Energy efficiency class	E	E	E	E
Refrigerant	R134a / R290	R134a / R290	R134a / R290	R134a / R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	242	307	392	588,4

## Standard equipment

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

internal cooling aggregate

static cooling (2 evaporators)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of white coated steel

rear storage compartment door - sliding (in the module 1.0 and corners - hinged)

grey granite worktop (thickness 20 mm)

internal frame and aluminum profiles anodised color silver or gold (IGLOO pattern book)

straight front glass pane (which can slightly be opened)

night blinds made of plexi glass

LED lamp (color of choice: white, confectionery or meaty "deep pink")

insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)

automatic defrost

---

automatic condenser vaporization

---

electronic temperature controller with digital display (IGLOO)

---

condenser impurity or fan operation failure alarm

---

## Options

device prepared for multiplexing

---

wooden sides + glass sides - selectable colour (IGLOO colour chart)

---

device without side panels prepared for multiplexing (MOD/A)

---

hinged system for the front window

---

housing with base panel from staff side made of stainless steel

---

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

---

front panel color - different colors available (IGLOO pattern book)

---

custom front panel color (after consultation with the IGLOO Sales Department)

---

base panel made of stainless steel

---

exposition area made of acid resistant stainless steel

---

storage chamber made of stainless steel

---

storage chamber made of acid - resistant stainless steel

---

exposition stepped overlay made of stainless steel (1 step)

---

exposition stepped overlay made of acid resistant stainless steel (1 step)

---

exposition stepped overlay made of stainless steel (2 step)

---

exposition stepped overlay made of acid resistant stainless steel (2 step)

---

powder painted evaporator

---

worktop - granite Balmoral (thickness : 20 mm)

---

worktop - granite black (thickness : 20 mm)

---

worktop - stainless steel

---

additional exposition glass shelf with illumination - LED light

---

set of wheels (castors)

---

automatic defrost

---

electronic temperature recorder + software

---

temperature recorder wire

---

socket with fuse

---

customer front shelf (aluminum profile anodised color silver or gold)

---

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart)

---

movable partition (low ,glass on stands , placed in exposition area)

---

top fixed partiton (high , glass in exposition area)

---

runner for small movable table

---

small movable table for scale or cash register (400x500mm)

---

