



Temperature range: **-24 ÷ -18 °C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290**

Name	ICECRAFT 1.2	ICECRAFT 1.6	ICECRAFT 2.0	ICECRAFT 2.5
Code	ICC120	ICC130	ICC140	ICC150
Length [mm]	1200	1600	2000	2500
Height [mm]	920	920	920	920
Depth [mm]	1050	1050	1050	1050
Capacity [dm ³]	224	309	395	501
Display area [m ²]	0,85	1,2	1,5	1,9
Total Display Area (TDA) [m ²]	-	-	-	-
Temp. range [°C]	(-24 ± -18°C)	(-24 ± -18°C)	(-24 ± -18°C)	(-24 ± -18°C)
Temp. class	3L1	3L1	3L1	3L1
Climate class	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)
Energy efficiency class	-	-	-	-
Refrigerant	R290	R290	R290	R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	1259	1655	1820	2097



The presented class applies to selected device modules. The classes for the individual modules may differ. The indication of the energy class for the selected device configuration is given on the attached label.

Standard equipment

internal unit

dynamic cooling (ventilated)

hot gas defrosting

automatic condensate evaporation – electric evaporator

electronic temperature controller with digital display

powder-coated display surface – choice of colour (IGLOO chart)

AC fans

LED lights – choice of colour: white, confectionery, or meat

side glazing units screen-printed in black or grey

thermometer in display space

Options

mesh partitions to keep the products in order

stainless steel bumpers

set of wheels (castors)

