



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Name	PICO DEEP 0.98	PICO DEEP 1.22	PICO DEEP 1.42	PICO DEEP 1.62	PICO DEEP 1.96	PICO DEEP 2.44
Code	MO200WG	MO201WG	MO202WG	MO203WG	MO204WG	MO205WG
Length [mm]	1060	1300	1500	1700	2040	2520
Height [mm]	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10
Depth [mm]	860	860	860	860	860	860
Capacity [dm ³]	160	210	240	270	330	410
Display area [m ²]	0,5	0,6	0,8	0,9	1,1	1,4
Total Display Area (TDA) [m ²]	-	-	-	-	-	-
Temp. range [°C]	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)
Temp. class	-	-	-	-	-	-
Climate class	-	-	-	-	-	-
Energy efficiency class	E	E	E	E	E	E
Refrigerant	R134a / R290	R134a / R290	R134a / R290	R134a / R290	R134a / R290	R134a / R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	286,4	286,4	290	365,4	365,4	450



The presented class applies to selected device modules. The classes for the individual modules may differ. The indication of the energy class for the selected device configuration is given on the attached label.

Standard equipment

internal cooling aggregate

dynamic cooling (ventilated)

body with service – side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of white coated steel

storage chamber back doors – hinged

worktop – stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

straight front glass pane (which can slightly be opened)

LED lamp (color of choice: white, confectionery or meaty “deep pink”)

bumper - different colors available (IGLOO pattern book)

insulated plastic side walls + glass side panels – different colors available (IGLOO pattern book)

automatic defrost

condenser outlet to container

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

wooden sides + glass sides - selectable colour (IGLOO colour chart)

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color – different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

display space with coloured sheet - selectable colour (IGLOO colour chart)

storage chamber made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid – resistant stainless steel

powder painted evaporator

night blinds made of plexi glass

worktop – granite grey (thickness : 20 mm)

worktop – granite Balmoral (thickness : 20 mm)

worktop – granite black (thickness : 20 mm)

additional exposition glass shelf

set of wheels (castors)

additional LED light in top lamp profile

automatic defrost

device with temperature range from -2 °C to +4 °C (includes electric defroster heaters)

automatic condenser vaporization

analog thermometer

electronic temperature recorder + software

temperature recorder wire

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart) (excludes the buffer)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

runner for small movable table

small movable table for scale or cash register (400x500mm)

box UVC - model 0.98 / 1.22 / 1.42 / 1.62

box UVC - model 1.96 / 2.44

PICO DEEP

