



Temperature range: **+1°C/+10°C**

Refrigerating unit:

Refrigerant/Cooling factor: **R290 / R448 / R449**

Name	OLA 1400.P
Code	OL100.P
Length [mm]	1635
Height [mm]	1980 +/-10
Depth [mm]	765
Capacity [dm <sup>3</sup> ]	1400
Display area [m <sup>2</sup> ]	4,4
Total Display Area (TDA) [m <sup>2</sup> ]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	-
Climate class	-
Energy efficiency class	C
Refrigerant	R290 / R448 / R449
Rated voltage [V]	230/50Hz
Rated power [W]	686

## Standard equipment

internal cooling aggregate placed on the bottom

dynamic cooling (ventilated)

external housing made of coated steel - different colors available (Igloo pattern book)

interior made of white coated steel

hinged doors

ecological polyurethane foam insulation

10 pcs ( 5 levels ) of plastified reticulated shelves, with height adjustment + bottom base shelf

automatic defrost

condenser outlet to container

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

## Options

external housing color – different colors available (IGLOO pattern book)

external housing made of stainless steel

interior made of stainless steel  
 fixed stainless steel partition panel (not tight)  
 horizontally divided doors  
 hinged doors self - closer  
 door lock with key  
 fan stopping switch  
 plastified strengthened shelves  
 chrome reticulated shelves  
 chrome strengthened reticulated shelves  
 additional plastified reticulated shelf + handle set  
 additional plastified reticulated strengthened shelf + handle set  
 additional chrome reticulated shelf + handle set  
 additional chrome reticulated strengthened shelf + handle set  
 internal top and side illumination - LED lights  
 internal rack with 18 drawers (9 levels) in stainless steel (excludes interior lighting)  
 automatic condenser vaporization  
 device with temperature range from -6 °C to 0 °C  
 electronic temperature recorder + software  
 temperature recorder wire  
 SMS alarm module + temperature recorder with emergency power supply  
 USB-MGSM TTL wire for SMS module programming

## OLA 1400.P

