



Temperature range: **-20°C/-10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Name	ARUBA 1.25	ARUBA 2.5
Code	AB101	AB102
Length [mm]	1385	2635
Height [mm]	1300+/-10	1300+/-10
Depth [mm]	1220	1220
Capacity [dm ³]	112	224
Display area [m ²]	0,85	1,7
Total Display Area (TDA) [m ²]	-	-
Temp. range [°C]	(-20 ± -11°C)	(-20 ± -10°C)
Temp. class	-	-
Climate class	-	-
Energy efficiency class	-	-
Refrigerant	R507 / R449A / R448 / R449	R507 / R449A / R448 / R449
Rated voltage [V]	230/50Hz	230/50Hz
Rated power [W]	1320	2655

Standard equipment

internal freezing aggregate

refrigerant system adapted for R448A / R449A

dynamic cooling (ventilated)

wooden external housing – different colors available (IGLOO pattern book)

glass sides

curved front glass - telescopic lifting system

ecological polyurethane foam insulation

exposition area made of stainless steel prepared for containers (360mm x 165mm) (ARUBA 1.25 = 14 flavours, ARUBA 2.5 = 28 flavours)

worktop – stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

manual shutter (from the personnel side)

upper interior lighting - fluorescent LED

automatic defrost

automatic condenser vaporization

IGLOO electronic temperature controller with digital display + electronic temperature recorder with software
condenser impurity or fan operation failure alarm

Options

scoop washer container

scoop washer container with water flow system

stainless steel container 360x165x120 mm

temperature recorder wire

