



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449 / R134a / R290**

Name	SANTIAGO 1.1S	SANTIAGO 1.4S	SANTIAGO 1.7S	SANTIAGO 2.1S	SANTIAGO 2.5S	SANTIAGO 3.75S
Code	SA100	SA101	SA102	SA103	SA104	SA180
Length [mm]	960	1290	1590	1920	2460	3750
Height [mm]	1225+/10	1225+/10	1225+/10	1225+/10	1225+/10	1225+/10
Depth [mm]	1190	1190	1190	1190	1190	1190
Capacity [dm ³]	171	214	257	321	407	621
Display area [m ²]	0,8	1,0	1,2	1,5	1,9	2,9
Total Display Area (TDA) [m ²]	0,59	0,78	0,96	1,21	1,47	2,25
Temp. range [°C]	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)
Temp. class	3H1	3H1	3H1	3H1	3H1	3H1
Climate class	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)
Energy efficiency class	D	D	D	D	E	E
Refrigerant	R290	R290	R290	R290	R290	R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	325	368	439	447	510	892

Standard equipment

insulated plastic side walls + glass side panels – different colors available (IGLOO pattern book)

static cooling

body with service – side base flashing composed of white, coated sheet metal

front base sheets and front panel with color – coated sheet – selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of stainless steel

storage chamber back doors – hinged

worktop – granite grey (thickness : 20 mm)

internal frame and aluminum profiles anodised color silver or gold (IGLOO pattern book)

curved front glass - telescopic lifting system

night blinds made of plexi glass

LED lamp (color of choice: white, confectionery or meaty “deep pink”)

bumper – different colors available (IGLOO pattern book)

insulated plastic side walls + glass side panels – different colors available (IGLOO pattern book)

automatic defrost

condenser outlet to container

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

wooden sides + glass sides – selectable color (IGLOO color guide)

device without side panels prepared for multiplexing (MOD/A)

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color – different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid – resistant stainless steel

exposition area – stepped – 2 steps

exposition area – stepped – 3 steps

powder painted evaporator

worktop – granite Balmoral (thickness : 20 mm)

worktop – granite black (thickness : 20 mm)

worktop – stainless steel

additional exposition glass shelf

set of wheels (castors)

fans enforcing air circulation

additional LED light in top lamp profile

automatic defrost

device with temperature range from – 2 °C to +4 °C (includes electric defroster heaters)

automatic condenser vaporization

analog thermometer

electronic temperature recorder + software

temperature recorder wire (RS232 – USB)

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart) (excludes the buffer)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

fixed insulated partition panel (increases the module length by 30mm)

runner for small movable table

small movable table for scale or cash register (400x500mm)

