



Temperature range: **+2°C / +4°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290**

Name	MAXIM 2 1.0	MAXIM 2 1.25
Code	MX2120	MX2130
Length [mm]	1030	1280
Height [mm]	920	920
Depth [mm]	1110	1110
Capacity [dm ³]	131	164
Display area [m ²]	0,9	1,1
Total Display Area (TDA) [m ²]	-	-
Temp. range [°C]	(+2 ± +4°C)	(+2 ± +4°C)
Temp. class	3H1	3H1
Climate class	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)
Energy efficiency class	-	-
Refrigerant	R290	R290
Rated voltage [V]	230/50Hz	230/50Hz
Rated power [W]	981	1406



The presented class applies to selected device modules. The classes for the individual modules may differ. The indication of the energy class for the selected device configuration is given on the attached label.

Standard equipment

internal cooling aggregate

internal cooling aggregate R290

dynamic cooling with automatic defrost

external housing made of coated steel sheet in a colour from the IGLOO pattern book

interior and display shelves made of color coated steel - different colors available (IGLOO pattern book)

front and sides screen printed in black or gray RAL 7042

set of wheels

the possibility of combining side-by-side

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

custom front panel color (after consultation with the IGLOO Sales Department)

interior and display shelves made of stainless steel

interior and display shelves made of acid-resistant stainless steel

powder painted evaporator

front buffer with stainless steel profile

set of sliding glass covers

display space thermometer

