OLA 2 NAP

Temperature range: **+1ºC/+10ºC**

Refrigerating unit:

Refrigerant/Cooling factor: **R290 / R448 / R449**

Name	OLA 1400.2
Code	OL100.2
Length [mm]	1635
Height [mm]	2000 +/10
Depth [mm]	785
Capacity [dm3]	1400
Display area [m²]	4,4
Total Display Area (TDA) [m²]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	-
Climate class	-
Energy efficiency class	C
Refrigerant	R290 / R448 / R449
Rated voltage [V]	230/50Hz
Rated power [W]	725

Standard equipment

dynamic cooling (ventilated)

internal cooling aggregate placed on the bottom

external housing made of black coated steel

interior housing made of black coated steel

hinged doors with combined glass

hinged doors self – closer

ecological polyurethane foam insulation

10 pcs (5 levels) of perforated shelves made of black coloured coated steel

black price strips

top panel illuminated with LED light –white plexiglass colour

automatic defrost

automatic condenser vaporization

innovative vertical interior lighting - LED light profiles 5700K - 4 pcs.

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

door lock with key	
additional perforated shelf + handle set	
electronic temperature recorder + software	
temperature recorder wire	

OLA 1400.2

pana cold